

## iR1020 Series (A4)

iR1020, iR1024A, iR1024F,  
iR1024i, iR1024iF

## imageRUNNER 2500 Series (A3)

imageRUNNER 2520/i, 2525/i,  
2530/i, 2535/i, 2545/i

**you can**

Compact black-and-white  
multifunctional printers  
for small-to-medium-  
sized workgroups.



ImageRUNNER

**Canon**

# Specifications: iR1020/iR1024 Series

<b>Type</b> Maximum Original Size Copy Sizes Resolution Copy/Print Speed Magnification First Copy Time Warm-Up Time Multiple Copies/Prints Duplexing Paper Weight Cassette Paper Capacity Standard Optional CPU Memory	<b>Desktop</b> A4 Cassette: A4, Stack Bypass: A5 - A4, Envelopes Copying: 600dpi x 600dpi Printing: 1200dpi equivalent x 600dpi (PCL, UFR II LT) 256 Gradations A4: 20cpm (iR1020), 24cpm (iR1024A/24F/24i/24iF) From Stack Bypass 23ppm (iR1024A/24F/24i/24iF) Zoom: 50-200%, Fixed: 50%, 70%, 100%, 141%, 200% 8.0 sec or less (iR1020), 12.0 sec or less (iR1024A/24F/24i/24iF) less than 16 sec for iR1020/24A/24F, less than 19 sec for iR1024i/24iF 1 to 99 sheets (Standard for all models) Automatic slackless Cassette: 64 to 90g/m <sup>2</sup> , Stack Bypass: 56 to 128g/m <sup>2</sup> , Duplex: 64 to 80g/m <sup>2</sup> A4 500 sheets x 1 cassette, Stack Bypass: 100 sheets 500 sheets x 1 cassette, Max. total paper capacity: 1,100 sheets Canon Custom Processor, 192MHz 128MB (iR1020/24A/24F), 256MB (iR1024i/24iF)
<b>Interface</b> <b>Power Supply</b> Power Consumption Dimensions (W x D x H) <b>Weight</b> <b>SEND FUNCTION<sup>1</sup></b> Scan Speed with DADF	iR1020/24A/24F Ethernet (100Base-TX/10Base-T) optional, USB2.0 iR1024i/iF Ethernet (100Base-TX/10Base-T), USB2.0 220V AC to 240V AC ±10% (50/60Hz) (W) 102.3W max. 520 x 457 x 378mm (iR1020) 520 x 457 x 453mm (iR1024A/24F/24i/24iF) Approx. 22.0kg (iR1020) Approx. 24.1kg (iR1024A/24F/24i/24iF) BW: 20ipm A4 300dpi, Colour: 6ipm A4 300dpi

<b>Scan Resolution</b> Destinations Address Book File Format	BW: Up to 600 x 600dpi, Colour: Up to 300 x 300dpi 300dpi (High compression PDF) E-Mail/Internet FAX (SMTP), PC (SMB, FTP), iWDM Gateway Local (Max. 200) TIFF, JPEG, PDF, High compression PDF
<b>PRINTER FUNCTION</b> PDL Resolution Memory CPU PCL Fonts Supported OS Interface Network Protocol	UFR II LT (Standard for iR1020/24A/24F/24i/24iF), PCL 5e/6 (Standard for iR1024i/24iF) 1200dpi equivalent x 600dpi (PCL, UFR II LT) 128MB (iR1020/24A/24F), 256MB (iR1024i/24iF) Canon Custom Processor, 192MHz (Uses Main Unit CPU) Roman 113 (including Barcode Fonts) PCL: Windows 2000/XP/Server 2003/Server 2008/Vista UFR II: Windows 2000/XP/Server 2003/Server 2008/Vista/ Mac OS X 10.2.8 or later iR1020/24A/24F Ethernet (100Base-TX/10Base-T) optional, USB2.0 iR1024i/iF Ethernet (100Base-TX/10Base-T), USB2.0 TCP/IP (LPD/RAW/Port 9100)
<b>DADF<sup>2</sup></b> Paper Size Paper Weight Scanning Speed (max.)	A4R, A5R, A5 50g/m <sup>2</sup> to 105g/m <sup>2</sup> A5R to A4: 50 sheets (80g/m <sup>2</sup> ) Copy: iR1024A/1024F/1024i/1024iF: A4 20ipm Scan BW: 20ipm A4 300dpi, Colour: 6ipm A4 300dpi
<b>OTHER ACCESSORIES</b>	iR1020/24 Plain Pedestal, Cassette Feeding Module N2, Cassette AD1, Card Reader-E1, Card Reader Attachment D2, NW IF ADAPTOR IN-E11 (Standard for iR1024i/24iF), PCL PRINT KIT-AB1 (Standard for iR1024i/24iF)
<sup>1</sup> Standard for iR1024i/24iF	<sup>2</sup> Standard for iR1024A/24F/24i/24iF

# Specifications: imageRUNNER 2500 Series

<b>Type</b> Maximum Original Size Copy Sizes Copy/Print Speed (BW) Magnification First Copy Time Warm-Up Time Multiple Copies/Prints Duplexing Paper Capacity CPU Memory	<b>Desktop or Free-standing, (Reader-Printer Combined)</b> A3 Cassette: A5R - A3 Stack Bypass: A5R - A3, Envelopes A4: 2545i/2545: 45ppm, 2535i/2535: 35ppm, 2530i/2530: 30ppm, 2525i/2525: 25ppm, 2520i/2520: 20ppm A3: 2545i/2545/2535i/2535: 22ppm, 2530i/2530/2525i/2525/ 2520i/2520: 15ppm Zoom: 25-400%, Fixed: 25%, 50%, 70%, 100%, 141%, 200%, 400% 3.9 sec: 2545/35, 5.4 sec: 2530/25, 6.4 sec: 2520 30 seconds 1 to 999 sheets Standard Standard: 2 x 550-sheet cassettes (80g/m <sup>2</sup> ), (1 x 250-sheet cassette for the imageRUNNER 2520i/2520) Cassette 1: 550 sheets (80g/m <sup>2</sup> ), (250 sheets for the 2520i/2520) Cassette 2: 550 sheets for 2525i, 2530i, 2535i, 2545i only Stack Bypass: 100 sheets (A4, A4R, A5), 50 sheets (A3) Optional: 550 sheets x 2 cassettes, 550 sheets x 1 cassette for imageRUNNER 2520/2520i only Total Capacity: 2,300 sheets, (2,000 sheets for the 2520i/2520) Canon Custom Processor, 400MHz 512MB (i models), 256MB (non i models)
<b>Interface</b> <b>Power Supply</b> <b>Power Consumption</b> Dimensions (W x D x H) <b>Weight</b>	Ethernet (100Base-TX/10Base-T), USB Host I/F 2.0, USB Device 1.0 220-240V AC, 50/60Hz, 4.2A (45/35ppm model), 220-240V AC, 50/60Hz, 3.3A (35/30/20ppm model) 1.827kW (45/35ppm model), 1.345kW (30/25ppm), 1.542kW (20ppm model) 2545i/2545/2535i/2535: 565 x 680 x 806mm, 565 x 689 x 907mm (with the DADF), 2530i/2530/2525i/2525: 565 x 680 x 806mm, 565 x 689 x 896mm (with the DADF), 2520i/2520: 565 x 680 x 681mm, 565 x 689 x 771mm (with the DADF) 2545i/2535i: Approx. 78.4kg, 2545/2535: Approx. 70.5kg 2530i/2525i: Approx. 77.5kg, 2530/2525: Approx. 68.0kg 2520i: Approx. 56.0kg, 2520: Approx. 50.5kg
<b>PRINT SPECIFICATION</b> PDL Resolution CPU Fonts Supported OS Interface Network Protocol Pull Scan	UFR II-LT, PCL5e/6 (standard on i models, optional on non i models), PostScript level 3 emulation (optional) 600 x 600dpi, 1200 x 1200dpi (UFR II-LT only) Canon Custom Processor, 400MHz PS Fonts: Roman 136; PCL Fonts: Roman 93 Windows 2000/XP/Server 2003/Vista/Server 2008/Windows 7, Mac OS X (10.4 or later), Linux Ethernet (100Base-TX/10Base-T) TCP/IP (LPD/Port9100, HTTP), SMB, SNMPv1, WSD, IPv4/IPv6 support Network TWAIN Driver
<b>SEND SPECIFICATION/ CLR SEND KIT-Y1</b> Scan Speed (A4, 300dpi, BW/Colour) Scan Resolution Destinations Address Book File Format	(standard on i models, optional on non i models) 45/34ipm (45/35ppm model), 25/13ipm (30/25/20ppm model) BW: Up to 600 x 600dpi, Colour: Up to 300 x 300dpi E-Mail/Internet FAX (SMTP), PC/Server (SMB, FTP), iWDM, USB memory key Local (Max.500) TIFF, JPEG, PDF, High compression PDF, Searchable PDF (with optional Searchable PDF-C1)

<b>DADF-AA1</b> Paper Size Paper Weight Max. Number of Originals Scanning Speed (max.) Dimensions (W x D x H) Weight	<b>for imageRUNNER 2545/2535</b> A3, A4, A4R, A5, A5R Single sided original: 42 to 128g/m <sup>2</sup> , Double-sided original: 50 to 128g/m <sup>2</sup> 100 sheets (A4, A4R, A5, A5R: 80g/m <sup>2</sup> ), 50 sheets (A3: 80g/m <sup>2</sup> ) Copy: 45ipm (A4, 600 x 600dpi) Scan: 45/34ipm 565 x 540 x 137mm Approx. 7.9kg
<b>DADF-AB1</b> Paper Size Paper Weight Max. Number of Originals Scanning Speed (max.) Dimensions (W x D x H) Weight	<b>for imageRUNNER 2530/2525/2520</b> A3, A4, A4R, A5, A5R Single sided original: 37 to 128g/m <sup>2</sup> , Double-sided original: 50 to 128g/m <sup>2</sup> 50 sheets (A4, A4R, A5, A5R: 80g/m <sup>2</sup> ), 25 sheets (A3: 80g/m <sup>2</sup> ) Copy: 25ipm (A4, 600 x 600dpi) BW) Scan: 25/13ipm 565 x 544 x 126mm Approx. 7.0kg
<b>CASSETTE UNIT-W1</b> Type Paper Size Paper Capacity and Weight Dimensions (W x D x H) Weight	<b>for imageRUNNER 2520/i</b> Front-loading adjustable drawers A3, A4, A4R, A5R, Custom size 139.7 to 297mm x 182 to 432mm 550 sheets (80g/m <sup>2</sup> ) x 1 cassette, 64 to 90g/m <sup>2</sup> 565 x 680 x 97mm Approx. 12.8kg
<b>CST. FEEDING UNIT-AE1</b> Type Paper Size Paper Capacity and Weight Dimensions (W x D x H) Weight	<b>for all models</b> 2 Front-loading adjustable drawers A3, A4, A4R, A5R, Custom size 139.7 to 297mm x 182 to 432mm 550 sheets (80g/m <sup>2</sup> ) x 2 cassettes, 64 to 90g/m <sup>2</sup> 565 x 680 x 248mm Approx. 24.0kg
<b>INNER FINISHER-B1</b> Number of Trays Tray Capacity Staple Position Staple Capacity Weight	<b>for all models</b> One stack tray (Optional 2nd Tray, Inner Fin Add. Tray-B1) A4-A5R: 1000 sheets, A3, A4R: 500 sheets Corner, Double A4: 50 sheets x 30 sets, A4R/A3: 30 sheets x 15 sets Approx. 12.5kg
<b>INNER 2-WAY TRAY-G1</b> Number of Trays Tray Capacity Weight	<b>for all models</b> 2 stack tray Tray A: 250 sheets (A4), 100 sheets (A3), Tray B: 100 sheets (A4), 50 sheets (A3) Approx. 0.6kg
<b>OTHER ACCESSORIES</b>	Platen Cover Type P, Platen Cover Type Q, Stamp Ink Cartridge-C1, ADF Access Handle-A1, PCL Printer Kit-AF1, PS Printer Kit-AF1, Barcode Printing Kit-B1, Super G3 Fax Board-AG1, FL Cassette-AU1, FL Cassette-AK1, FL Cassette-AL1, Cassette Spacer-A1, imageRUNNER 2500 Plain Pedestal, 2-Way Unit-B1, Staple-J1, Document Tray-J1, Power Supply Unit-U1, Card Reader Attachment-D3, Canon Card Reader-E1, USB Application 3-Port Interface Kit-A1, CCV1 I/F Cable-A1, C-EXV33 TONER BK (imageRUNNER 2520/i, 2525/i, 2530/i), C-EXV32 TONER BK (imageRUNNER 2535/i, 2545/i)
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. ™ and ©: All company and/ or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.	

