# FS-6025MFP / FS-6030MFP

MONOCHROME MULTIFUNCTIONALS



# COMPACT, HIGHLY EFFICIENT MULTIFUNCTIONAL PRINTERS

These new multifunctional devices offer all the benefits of a professional document management solution for workgroups and small offices. Featuring advanced functionality, easy to operate touchscreen, and a range of paper-handling options, all in a well-designed compact package. Cost-efficient and eco-friendly offices will appreciate KYOCERA's unique ECOSYS™ technology which increases operating life, reduces environmental impact, cuts printing costs and ensures reliability.

- ▶ Up to 30 A4 pages per minute
- ► Time to first copy: 9.2 seconds or less
- ▶ Professional print, copy, scan and fax functionality †
- ▶ Paper capacity up to 1,600 sheets and a range of paper-handling options
- Easy to install and operate
- ► Easy to use wizard-style navigation
- ► Low noise emissions match desktop printers
- ► Compact, 360° all-round stylish design to match any office
- ► ECOSYS<sup>™</sup> Long-life components provide unprecedented efficiency and reliability
- ► Exceptionally low printing costs in its class





# FS-6025MFP / FS-6030MFP

# MONOCHROME MULTIFUNCTIONAL FOR A4/A3 FORMAT

## The FS-6025MFP / FS-6030MFP includes:

With the KYOCERA page design and control language PRESCRIBE, even complex graphics, logos and forms (multipart forms) can be created independently on the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

The KM NetViewer enables complete monitoring and control of all ECOSYS printers and digital KYOCERA multifunction units from any Windows© PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

### Status Monitor and Command Centre

The Status Monitor shows the current printers condition and gives direct access to the Command Center for the modification of settings that are not contained in the drivers (e.g. network settings, adjustment of sleep mode or blocking of the control panel).

PDF files can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. Documents are selected directly via the printer's control panel. No computer is required.

### **Our Unique Printing Technology**

**Ecosys** Ecosys stands for Ecology, Economy and SYStem-printing. With long-life components, ECOSYS devices are designed to maximise durability and min-imise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly, and the drum units every 300,000 pages. The modular design concept allows you to add workflow-enhancing functions as required. Integrated system software provides long-term cross-network compatibility. KYOCERA's long-life components cost you and the environment less.

Technology: KYOCERA ECOSYS, Mono Laser Engine speed: FS-6025MFP - Up to 25 pages A4 per minute FS-6030MFP - Up to 30 pages A4 per minute

Resolution: 600 x 600 dpi (print, copy and scan)

PM cycle: 300,000 pages

Warm-up time: Approx. 20 seconds or less Time to first print: Approx. 8 seconds or less Time to first copy: Approx. 9.2 seconds or less

CPU: PowerPC 464 / 800 MHz

Memory: Standard 512 MB, max. 1,536 MB Integrated accounting: 20 department codes Dimensions (W x D x H): 590 x 590 x 694 mm Weight: Approx. 52.2 kg including toner container

Power source: AC 220 ~ 240 V, 50/60 Hz Safety standards: AS / NZ53260 / C-TICK

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

All paper capacities quoted are based on a paper thickness of max. 0.11 mm (80gsm). Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: 100-sheet multi-purpose tray, 45-256 gsm, 200 mm (Postcard): 52-163 gsm (larger than A4 / Letter size), A3, A4, A5, A6, B5, Letter, Legal, Folio envelopes, Custom (98 x 148 to 297 x 432 mm) 500-sheet universal paper cassette, 60-256 gsm, A3, A4, A5, A6, B5, Letter, Legal, Folio, max. input capacity with options:

Duplex unit: Duplex as standard supports 60-163 gsm A3-A5R

**Reversing document processor:** 50-sheet, Simplex scan 45–160 gsm, Duplex scan 50–120 gsm, A3, A4, A5, B5, Letter, Legal, Custom (140 x 182 to 297 x 432 mm)

Output capacity: Max. 300 sheets: 250 sheets face-down (main tray), plus 50 sheets (job separator tray)

Controller language: PRESCRIBE

Emulations: PCL 6 (5e/XL), KPDL 3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print

Interface: USB 2.0 (High-Speed), USB Host 2.0, Fast Ethernet 10/100/1,000Base-TX, Slot for optional print server, Slot for optional Memory Card

Operating systems: All current Windows operating systems, MAC OS X Version 10.2 or higher, Unix, Linux as well as other operating systems on request

Fonts/bar codes: 93 outline fonts (PCL 6, KPDL3) + 8 (Windows Vista), OCR: OCR-A, OCR-A kana, OCR-B, OCR-B kana, OCRkana bitmap fonts, 45 types of one-dimensional bar codes, 1 type of two-dimensional bar code (PDF 417) - via PRESCRIBE

Features: encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3

## Max. original size: A3/Ledger

Continuous copying: 1-999 Zoom range: 25-400% in

Preset magnification ratios: 5 Reductions / 5 Enlargements Features: Scan-once-copy-many, sort, 2in1, 4in1, job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change (PF-470 or PF-471 is

required), copy density control, Prevent Bleed-Through Exposure mode: Auto, manual: 7 steps

Image adjustments: Text, Photo, Text + Photo, Graphic/ Map, Copy/Printout

 $\begin{tabular}{ll} \textbf{Functionality:} & \textbf{Scan-to-Email, Scan-to-FTP, Scan-to-PC, Scan to USB Host, TWAIN, WSD scan} \end{tabular}$ 

Interface: Fast Ethernet 10/100Base-TX, USB Host 2.0 Scan speed: 40 ipm (300 dpi, A4, b/w), 20 ipm (300 dpi,

A4 colour)

Scan resolution: 600, 400, 300, 200 dpi (256 greyscales

per colour)

Max. scan size: A3, Ledger File types: TIFF, PDF, JPEG, XPS

**Features:** Integrated address book, encrypted data transfer, multi send (e-mail, fax, SMB/FTP folder, print) at once

Compatibility: ITU -T Super G3 Modem speed: Max. 33.6 kbps Transmission speed: Less than 3 sec

Scanning speed: 2.0 seconds (Quick Scanning, Bitmap)

Address book: 200 entries

Interface: Fast Ethernet 10/100/1000Base-TX, Telephone interface

## Scanning density:

Normal: 8 dot/mm x 3.85 line/mm Fine: 8 dot/mm x 7.7 line/mm Superfine: 8 dot/mm x 15.4 line/mm Ultrafine: 16 dot/mm x 15.4 line/mm Halftone: 8 dot/mm x 7.7 line/mm Maximum original size: A3. Ledger

Compression method: JBIG, MMR, MR, MH Memory reception: 700 sheets or more

Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

### Paper handling

**PF-470 Paper feeder:** Max. 500 sheets; 60–163 gsm; A3, A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm) PF-471 Paper feeder: Max. 1,000 sheets; 60-163 gsm; A3, A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm) **DF-470 Document finisher:** Max. 500 sheets 52-256 gsm; A3, A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm) AK-470 Bridge Unit: To be used with DF-470

### Memory upgrade

DIMM-512 MBP: 512 MB; DIMM-1GBP: 1024 MB

### Others

USB Flash Memory: Supports direct printing and scanning of PDF, XPS,TI FF, JPEG files via USB Host interface

**Optional Interfaces** 

Fax System: Type U

Additional network card: IB-50

TK-479 Toner Kit: Microfine toner black for 15,000 pages A4 in accordance with ISO/IEC 19752

Capacity of starter toner is 3,000 pages in accordance with ISO/IEC 19752

3-year warranty as standard to a maximum 180,000 pages for FS-6025MFP and 150,000 pages for FS-6030MFP - whichever occurs sooner, provided the printer is used and cleaned in accordance with the service instructions.







Windows Vista and the Windows Vista logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries.

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged. † The fax functionality is an optional feature.

# **KYOCERA MITA Australia**

Ph: 13 KYOCERA

www.kyoceramita.com.au

**KYOCERA MITA New Zealand** 

Ph: 0508 KYOCERA

www.kyoceramita.co.nz



we'll save you the Earth

The images displayed in this brochure are for illustrative purposes only, and may include optional extras.